

TEREX ECOTEC PRODUCT RANGE



SLOW SPEED SHREDDERS



TDS 820

Scania DC13 331kW (440HP) Stage V Engine: Scania DC13 331kW (440HP) Tier 4 Final Scania DC13 371kW (497HP) Stage IIIA

Constant Speed 27,500kg (60,627lbs) (Depending On Options)

TROMMEL SCREENS

Shaft Length: 2m Twin Shaft

(f) Electric / Hydraulic Option



TDS 825

Scania DC16 566kW (770HP) Stage V Scania DC16 566kW (770HP Tier 4 Final Scania DC16 566kW (770HP) Stage II

46,500kg (102,514lbs) (Depending On Options)

Shaft Length: 2.5m Twin Shaft

Wheeled or Tracked Variants

TSS 390/T

Shaft Length: 3m Single Shaft

MEDIUM SPEED SHREDDER



TDS V20

Scania DC13 368kW (493HP) Stage V Scania DC13 368kW (493HP) Tier 4 Final Scania DC13 371kW (497HP) Stage IIIA

Constant Speed Weight: 37,000kg (81,571lbs) (Depending On Options)

Shaft Length: 2m Twin Shaft

(7) Electric / Hydraulic Option

HIGH SPEED SHREDDERS



TBG 530T

Scania DC13 368kW (493HP) Stage V Scania DC13 368kW (493HP) Tier 4 Final Scania DC13 368kW (493HP) Stage II

Rotor Width: 1.490mm (4'11") Weight: 26,500kg (58,422lbs) Feed Opening: 1,436mm x 700mm (4'9" x 2'4")

Weight: 35,600kg (78,485lbs)

TBG 630

Feed Opening: 1,700mm x 780mm (5'7" x 2'7")

Rotor Width: 1.750mm (5'9")

RECYCLING SCREEN



TTS 518/T

CAT C2.2 55kW (74HP) Stage V / Tier 4 Final Engine: CAT C4.4 62kW (83HP) Stage IIIA

18,000kg (39,683lbs) Tracked

Drum Ø x Length: 1.8m x 4.7m (5'1" x 15'5") 17,200kg (37,920lbs) Wheeled

Wheeled or Tracked Variants



TTS 620/T

CAT C4.4 98kW (131HP) Stage IIIA Constant Speed CAT C4.4 102kW (137HP) Stage V / Tier 4 Final

Drum Ø x Length: 2m x 5.5m (6'7" x 18'1") 19,000kg (41,888lbs) Wheeled 24,000kg (52,911lbs) Tracked

Wheeled or Tracked Variants 🕖 Electric / Hydraulic Option - Wheeled Only

Deutz TCD 3.6 L4 85kW (114HP)

Stage V / Tier 4

14,600kg - 17,100kg

(Without Attachments)

(32,187lbs - 37,699lbs)

WASTE HANDLERS

TWH 216

Max. Reach: 9.0m (29')



Scania DC13 368kW (493HP) Stage V

Scania DC13 368kW (493HP) Tier 4 Final

Scania DC13 368kW (493HP) Stage II

32,000kg (70,548lbs) (Depending On Options)

Phoenix 1600/T

CAT C4.4 82 kW (110HP) Tier 4 Final CAT C4.4 102kW (137HP) Stage V / Tier 4 Final CAT C4.4 98kW (131HP) LRC

Drum Ø x Length: 1.54m x 4.9m (5' x 16') 18,000kg (39,700lbs) Wheeled 21,100kg (46,500lbs) Tracked

Wheeled or Tracked Variants



Phoenix 2100/T

CAT C4.4 129kW (173HP) Tier 4 Final CAT C4.4 129kW (173HP) Stage V / Tier 4 Final CAT C71 151kW (202HP) LRC CAT C4.4 102kW (137HP) Stage V / Tier 4 Final (T)

CAT C4.4 98kW (131HP) LRC (T)

Drum Ø x Length: 1.94m x 6.45m (6'4" x 21'2") 27,500kg (60,627lbs) Wheeled 31,000kg (68,380lbs) Tracked

Wheeled or Tracked Variants Flectric / Hydraulic Option



Phoenix 3300

CAT C4.4 129kW (173HP) Tier 4 Final CAT C4.4 129kW (173HP) Stage V / Tier 4 Final CAT C7.1 151kW (202HP) LRC

Drum Ø x Length: 2.32m x 9.32m (7'7" x 30'7") 37,500kg (82,673lbs)

Flectric / Hydraulic Option



Scania DC16 500kW (670HP) Stage V

Scania DC16 515kW (690HP) Stage II

Scania DC16 493kW (661HP) Tier 4 Final

TRS 550

CAT C4.4 83kW (111HP) Tier 3 Equivalent CAT C4.4 82 kW (110HP) Tier 4 Final

CAT C4.4 102kW (137HP) Stage V / Tier 4 Final Screenbox Style: 3D Top Deck & Flip Flow Bottom Deck Screenbox Size: 4.8m x 1.53m (16' x 5') Top & Bottom Deck

30,500kg (67,240lbs)

Dual Power Option

Weight:

METAL SEPARATOR

TMS 320

60kVa Tier 3 60kVa Stage V / Tier 4 Final

2m Wide - Rare Earth Drum Magnet: Eddy Current Rotor: 2m Wide - 22 pole 19,500kg (42,990lbs) (Depending On Options)

Electric / Hydraulic Option



TWH 220

Deutz TCD 3.6 L4 95kW (127HP) Stage V / Tier 4 Deutz TCD 3.6 L4 95kW (127HP) Stage IIIA / Tier 3

Max. Reach: 10.4m (34'1") 19,300kg - 21,000kg (42,549lbs - 46,297lbs) (Without Attachments

Flectric / Hydraulic Option



TWH 224

Deutz TCD 4.1 L4 115kW (154HP) Stage V / Tier 4 Deutz TCD 4.1 L4 115kW (154HP) Stane IIIA / Tier 3

Max. Reach: 12.0m (39'4") 22,800kg - 24,200kg (50.265lbs - 53.352lbs) (Without Attachments)

Flectric / Hydraulic Option



TWH 226

Deutz TCD 4.1 L4 115kW (154HP) Stage V / Tier 4 Deutz TCD 4.1 L4 115kW (154HP)

Stane IIIA / Tier 3 12.0m (39'4") Max. Reach: 23.900ka - 25.500ka (52.690lhs - 56.218lhs)

(Without Attachments)

Flectric / Hydraulic Option



TWH 228

Deutz 6.1 L6 129kW (173HP) Stage V / Tier 4 Deutz TCD 2012 L06 2V 128kW (172HP) Stage IIIA / Tier 3

Max. Reach: 13.7m (44'11") 28,400kg - 30,600kg (62.611lhs - 67.462lhs) (Without Attachments)

Flectric / Hydraulic Option



TWH 236

Deutz TCD 6.1 L6 160kW (215HP) Stage V / Tier 4 Deutz TCD 2013 L6 148kW (198HP)

Stane IIIA / Tier 3 Max. Reach: 16.0m (52'6") 33,000kg - 35,500kg

(72.753lhs - 78.264lhs) (Without Attachments)

Flectric / Hydraulic Option



Deutz TCD 7.8 L6 4V 190kW (255HP) Stage V / Tier 4

Deutz TCD 2013 L06 2V 186kW (249HP) Stage IIIA / Tier 3 Max. Reach: 18.0m (59'1")

43,500kg - 48,800kg (95.901lhs - 107.586lhs) (Without Attachments)

Flectric / Hydraulic Option



TSC 65T

Conveyor Length: 19.79m (64'11") Belt Width: 1050mm (42") Max. Discharge Height: 9.45m (31')



TSC 80T

Conveyor Length: 22.8m (74'10") Belt Width: 1050mm (42") Max. Discharge Height: 10.41m (34'2")



TSC 100T

Conveyor Length: 30.1m (98'9") Belt Width: 1050mm (42") Max. Discharge Height: 13.1m (42'12")



TRC 75

Conveyor Length: 22.9m (75'2") Belt Width: 1050mm (42") Max. Discharge Height: 10.9m (35'9")



TFC 75

22.5m (73'10") Conveyor Length: Belt Width: 1200mm (47") Discharge Conveyor

1200mm (47") Feed Conveyor Max. Discharge Height: 9.8m (32'2")



TFC 75L

Conveyor Length: 22.5m (73'10")

Belt Width: 1200mm (47") Discharge Conveyor

1300mm (51") Feed Conveyor

Max. Discharge Height: 9.8m (32'2")



TFC 75 Organics

Conveyor Length: 22.5m (73'10")

Belt Width: 1200mm (47") Discharge Conveyor

1400mm (55") Feed Conveyor

Max. Discharge Height: 9.8m (32'2")



TFC 75 Organics Orbital

Conveyor Length: 22.5m (73'10")

1200mm (47") Discharge Conveyor Belt Width: 1400mm (55") Feed Conveyor

Max. Discharge Height: 10.7m (35'1")



TFC 75 Orbital

Conveyor Length: 22.5m (73'10")

Belt Width: 1200mm (47") Discharge Conveyor

1200mm (47") Feed Conveyor

Max. Discharge Height: 10.7m (35'1")



TFC 75L Orbital

Conveyor Length: 22.5m (73'10")

1200mm (47") Discharge Conveyor Belt Width:

1300mm (51") Feed Conveyor

Max. Discharge Height: 10.7m (35'1")



TSC 80

Conveyor Length: 22.85m (74'12") Belt Width: 914mm (36") Max. Discharge Height: 9.22m (30'2")

Dealer Stamp:







