



**TEREX®**

**Terex® Minerals Processing Systems  
Cedarapids RC45III**



**Quick  
Adjust,  
No Shims**



Simple, Manual Hydraulic Controls

# RC45III CONE CRUSHER

**Hydraulic Adjustment System Allows Quick and Easy Setting Changes**

## KEY FEATURES AND BENEFITS

- ▶ 200 hp (149 kW) 45" (1143 mm) high production cone crusher
- ▶ Hydraulic thread adjust makes crusher setting changes quick and easy (no shims)
- ▶ Manganese rotates for uniform wear, longer life, and consistent product sizing
- ▶ Manganese and internal drive components are interchangeable with the RC45II
- ▶ Proven Rollercone® reliability and performance
- ▶ Efficient roller bearing design for low cost per ton of operation
- ▶ Field proven quick reset hydro-pneumatic tramp iron relief system
- ▶ Accumulators protected within upper assembly
- ▶ Heavy-duty cast base frame for long life and low maintenance

**[www.terexmps.com](http://www.terexmps.com)**

Effective Date: March 2012. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and Terex makes no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation and/or its subsidiaries in the USA and other countries. All rights are reserved. Terex is a registered trademark of Terex Corporation in the USA and many other countries. © 2012 Terex Corporation.

Terex® Minerals Processing Systems, 909 17th Street NE, Cedar Rapids, IA 52402 USA  
Tel +1 319 363 3511 Fax +1 319 399 4871 [www.terexmps.com](http://www.terexmps.com)

Form 24936 (3/12)